



## General characteristics

Description	Value	Unit
<b>Dimensions</b>		
Width	750	mm
Depth	460	mm
Height	190	mm
Weight	33	kg

<b>Electrical characteristics</b>		
Input voltage	100-240	Vac
Input voltage net tolerance	±10	%
Input voltage frequency	50/60	Hz
Max. input current	5.9-2.7	A
Power mains supply voltage fluctuations	±10	%
Installation category	CAT II	-
Input fuse type	250VAC, 8A, time-lag	-

C.NEST®

# Spec sheet

## Operating/ storage environment

Description	Value	Unit
<b>Required ambient conditions</b>		
Min. temperature	20	°C
Max. temperature	30	°C
Min. rel. humidity (non-condensing)	20	%
Max. rel. humidity (non-condensing)	60	%
Max. altitude for operation	2,000	m
Indoor use	Yes	-
Outdoor use	No	-
Pollution degree	2	-
Minimum space between the surrounding walls and instrument	100	mm

Each value above is specified with one standard deviation from its mean ( $M \pm 1SD$ )

Learn more: [cytena-bps.com/c-nest](https://cytena-bps.com/c-nest)

## Basic configuration

Description	Value	Unit
<b>Incubation</b>		
Temperature control range	RT+10-40±0.2	°C
CO <sub>2</sub> level control range	1-20	%
CO <sub>2</sub> accuracy*	±0.3	%
<b>Humidity monitoring range</b>	0-100±5 (at 37°C)	%
<b>Culture</b>		
Mixing rate (24-well plate)	10-50 (±5%)	sec
Mixing rate (96-well plate)	10-50 (±5%)	sec
Working volume (24 well plate)	1,000-1,600	µl
Working volume (96-well plate)	150-200	µl

\*The range of deviation is based on a 5% CO<sub>2</sub> set point and may vary with adjustments or if recalibration is needed.

### CONTACT

Email: [info@cytena-bps.com](mailto:info@cytena-bps.com) | Taiwan phone: (+886) 2-2720-6135

**CYTENA BPS**   
A BICO COMPANY